

## SHIELDED ANGLED MODULAR PATCH PANEL 48P 2U



---

<b>Product Type</b>	Patch Panel
---------------------	-------------

---

<b>Product Family</b>	FISACCESSO
-----------------------	------------

---

<b>Standard</b>	ROHS Compliant
-----------------	----------------

---

### Applications

---

<b>Installation Environment</b>	Indoor
---------------------------------	--------

---

<b>Operation Environment</b>	Non Aggressive
------------------------------	----------------

---

<b>Compatibility</b>	All FCS products
----------------------	------------------

---

<b>Warranty</b>	12 months
-----------------	-----------

---

### Advantage

- Shielded Angled Patch Panel;
- 48 unloaded positions and 2U height;
- It has a rear terminal for grounding wire connection;
- Electrical conductive bond to automatically ground the shielded keystone jacks;
- Resistant and corrosion-protected product for the conditions specified for indoor use (TIA/EIA 569);
- Displays width of 19" according to requirements of the standard TIA/EIA-310E;
- All positions are numbered allowing connections identification;
- Enables insertion of icons (blue and red colors included);
- Identification label with acrylic cover included;
- Allows scalability as plant grows;
- Product developed for high-density, not requiring the use of a horizontal cable manager, although an adequate vertical cable manager is necessary;
- Saves rack space;
- Provides easier installation of patch cords;
- Compatible with keystone Jack CAT.5E, CAT.6 and CAT.6A F/UTP;
- Compatible with all Furukawa female connectors, F modules and optical with optical adapter assembly;
- Supplied with fixing screws.

---

<b>Identification</b>	Furukawa frontal logo
-----------------------	-----------------------

---

### Constructive characteristic

---

<b>Height</b>	88.10mm (2U)
---------------	--------------

---

<b>Width</b>	482.6mm (19")
--------------	---------------

---

<b>Depth</b>	110 mm
--------------	--------

---

<b>Metal thickness</b>	1.5mm
------------------------	-------

---

<b>Painting thickness</b>	0.1 mm
<b>Painting Type</b>	Epoxy
<b>Color</b>	Black
<b>Connector Type</b>	RJ-45 shielded
<b>Number of Ports</b>	48 Positions
<b>Material of Product body</b>	Steel SAE1020 / Steel - nickel
<b>Accessories Included</b>	Mounting screws
<b>Package</b>	
<b>Package Type</b>	Cardboard
<b>Amount per box gift</b>	01 piece
<b>Amount per box (carton)</b>	01 piece
<b>Dimension (WHD)</b>	520 x 110 x 130 mm
<b>Associated Solutions</b>	Cable and accessories management
<b>Standards and Certifications</b>	
<b>Standard</b>	ANSI/TIA-569-D Telecommunications Pathways and Spaces
	EIA-ECA-310-E Cabinets, Racks, Panels, and Associated Equipment