

SHIELDED ANGLED MODULAR PATCH PANEL 24P 1/2U

Product Type	Patch Panel
Product Family	FISACESSO
Standard	ROHS Compliant

Applications

Installation Environment	Indoor
Operation Environment	Non Aggressive
Compatibility	All FCS products
Warranty	12 months

Advantage

- Angled Patch Panel for High density;
- 24 unloaded positions and 1/2U (half U) height;
- It has a rear terminal for grounding wire connection;
- Electrical conductive bond to automatically ground the shielded keystone jacks;
- Resistant and corrosion-protected product for the conditions specified for indoor use (TIA/EIA 569);
- Displays width of 19" according to requirements of the standard TIA/EIA-310E;
- All positions are numbered allowing connections identification;
- Allows scalability as plant grows;
- Compatible with keystone Jack CAT.5E, CAT.6 and CAT.6A F/UTP;
- Compatible with all Furukawa female connectors, F modules and modules with optical adapters;
- Supplied with fixing screws;
- Supplied with rear cable manager.

Constructive characteristic

Height	22.2mm (1/2U)
Width	482.6mm (19")
Depth	110 mm
Metal thickness	1.5mm
Connector Type	RJ-45, SC, LC, F and blank panel
Number of Ports	24 positions.
Material of Product body	Steel SAE1020



Accessories Included

• Fixing screws.

Package	
Package Type	Cardboard
Amount per box gift	01 piece
Associated Solutions	Cable and accessories management
Standards and Certificat	ions
Standard	ANSI/TIA-569-D Telecommunications Pathways and Spaces
	EIA-ECA-310-E Cabinets, Racks, Panels, and Associated Equipment
	NMX-I-248-NYCE-2008

