



MODULAR PATCH PANEL 24P 1/2U

Product Type TELECOMMUNICATION INFRASTRUCTURE ACCESSORY

Product Family FISACCESSO

Standard RoHS Compliant

Applications

Installation Environment Indoor

Operation Environment Indoor no aggressive

Compatibility All FCS products

Warranty 12 months

Advantage

- Patch Panel for High density;
- 24 unloaded positions and 1/2U (half U) height;
- Resistant and corrosion-protected product for the conditions specified for indoor use (TIA/EIA 569);
- Displays width of 19" according to requirements of the standard TIA/EIA-310E;
- All positions are numbered allowing connections identification;
- Allows scalability as plant grows;
- Compatible with keystone Jack CAT.5E, CAT.6 and CAT.6A U/UTP;
- Compatible with all Furukawa female connectors, F modules and modules with optical adapters;
- Supplied with fixing screws;
- Supplied with rear cable manager.

Constructive characteristic

Width 482.6 mm

Height 22.2mm (1/2U)

Depth 31 mm

Material of Product body Steel SAE1020

Metal thickness 1.5mm

Color Black

Painting Type Epoxy

Painting thickness 0.1mm

Connector Type RJ-45

Number of Ports 24 ports

Accessories Included

- Rear cable manager;
- Fixing screws.

Package

Package Type Cardboard

Amount per box gift 01 piece

Associated Solutions Management of cables and accessories

Standards Compliance

Standard TIA/EIA - 569 C - COMMERCIAL BUILDING STANDARD FOR TELECOMMUNICATIONS PATHWAYS AND SPACES

TIA/EIA - 310 E - CABINETS, RACKS, PANELS, AND ASSOCIATED EQUIPMENT
