

19" FURUKAWA RACK

- 19" FURUKAWA RACK design & produce under ANSI/EIA-310D – 1992 (Rev.EIA-310-C),2 IEC60297-1, IEC 60927-2, BS 5954 : Part2, DIN 41494 standard
- Modular knock down system for easily transport & assembly
- Produced from Electro-Galvanized Steel
 - Front – Rear, Side cover material thickness 1.5mm.
 - Mounting Angle Pole , Frame structure, Bottom Base material thickness 2.0mm.
 - Support base for Caster material thickness 3.0mm.
- Special design Mounting Angle Pole in C-shape for increasing strength for heavy equipment with square mounting hole size 7.0x7.0mm.
- Adjustable Mounting Pole position with U screen for easily installation.
- Front door panel attached with premium grade Acrylic thickness 5mm. Grey rubber also attached for each door to protect dust. The front door come with security Cam lock with master key system.
- Rear door panel designed for ventilating size 34x23cm. Come together with filter which easily for cleaning. Grey rubber also attached for each door in order to protecting from dust. The rear door come with security camlock with master key system.
- 3 Premium grade PVC Hinges for each door were attached with easily open and close. The frame structure also provided the common hole for any users for easily swap the direction when open-close the door by themselves.
- Side Panels come together with 2 Premium grade slide latches per panel and security cam lock with master key system
- Roof Cover also designed for installing up to 6 ventilating fan which compatible with 1x 4", 2x4", 3x4" fan set
- Bottom Base also designed for heavy load with soft slide shutter function for all cables. Soft slide shutter also come with the soft grey sponge to protect insect and small animals to enter the rack from bottom.
- Adjustable levelling feet for aligns on uneven surface also cover with ABS material in order to protect Electrostatic and ground reason.
- Caster is Nylon six and 360 degree swivel plate which can be easily moving. Each caster can pass static load of 100 kg./caster.
- Rack Color is New Shine Two-Tone (Light Grey-Dark Grey) which using Electro static Powder Coating system
- For Grounding system also installing 2 ground cable size 2.5mm (Yellow-green color) length 18cm.connect the frame with front and rear door. For side panels also intall 4 ground cable (Yellow-green color) length 13cm.
- Screw sets consist of M6 screw, Captive nut, Plastic washer. Screw and captive nut is Nickel plating.
- 19" FURUKAWA RACK are manufactured under ISO9001 : 2008 and ISO 14001 system.



		19" FURUKAWA RACK						
		U	15U	27U	36U	39U	42U	45U
W=60cm	Height							
	Depth	85cm	139cm	179cm	185cm	205cm	218.5cm	
	60cm	F3-60615	F3-60627	F3-60636	F3-60639	F3-60642	F3-60645	
	80cm	F3-60815	F3-60827	F3-60836	F3-60839	F3-60842	F3-60845	
	90cm	F3-60915	F3-60927	F3-60936	F3-60939	F3-60942	F3-60945	
	100cm	F3-61015	F3-61027	F3-61036	F3-61039	F3-61042	F3-61045	
	110cm	F3-61115	F3-61127	F3-61136	F3-61139	F3-61142	F3-61145	
W=80cm	U	15U	27U	36U	39U	42U	45U	
	Height							
	Depth	85cm	139cm	179cm	185cm	205cm	218.5cm	
	80cm	F3-80815	F3-80827	F3-80836	F3-80839	F3-80842	F3-80845	
	90cm	F3-80915	F3-80927	F3-80936	F3-80939	F3-80942	F3-80945	
	100cm	F3-81015	F3-81027	F3-81036	F3-81039	F3-81042	F3-81045	
	110cm	F3-81115	F3-81127	F3-81136	F3-81139	F3-81142	F3-81145	

