

19" FURUKAWA SERVER RACK

- 19" FURUKAWA SERVER RACK design & produce under ANSI/EIA-310D – 1992 (Rev.EIA-310-C), IEC60297-1, IEC 60927-2, BS 5954 : Part2, DIN 41494 standard
- Modular knock down system for easily transport & assembly
- Produced from Electro-Galvanized Steel
 - Front – Rear, Side cover material thickness 1.5mm.
 - Mounting Angle Pole , Frame structure, Bottom Base material thickness 2.0mm.
 - Support base for Caster material thickness 3.0mm.
- Special design 4 Mounting Angle Pole in C-shape for increasing strength for heavy equipment with square mounting hole size 9.5x9.5mm.
- Adjustable Mounting Pole position with U screen for easily installation.
- Front door panel is perforated attached with premium grade Acrylic thickness 5mm. Grey rubber also attached for each door to protect dust. The front door is security Locks by swing handle with master key system.
- Rear door is full perforated panel. Grey rubber also attached for each door to protect dust. The rear door come with security camlock with master key system.
- 3 Premium grade PVC Hinges for each door were attached with easily open and close. The frame structure also provided the common hole for any users for easily swap the direction when open-close the door by themselves.
- Side Panels come together with 2 Premium grade slide latches per panel and security cam lock with master key system Roof
- Cover also designed for installing up to 6 ventilating fan which compatible with 1x 4" , 2x4" , 3x4" fan set
- Bottom Base also designed for heavy load with soft slide shutter function for all cables. Soft slide shutter also come with the soft grey sponge to protect insect and small animals to enter the rack from bottom.
- Adjustable levelling feet for aligns on uneven surface also cover with ABS material in order to protect Electrostatic and ground reason.
- Caster is Nylon six and 360 degree swivel plate which can be easily moving. Each caster can pass static load of 100 kg./caster.
- Rack Color is New Shine Two-Tone (Light Grey-Dark Grey) which using Electro static Powder Coating system
- For Grounding system also installing 2 ground cable size 2.5mm (Yellow-green color) length 18cm.connect the frame with front and rear door. For side panels also intall 4 ground cable (Yellow-green color) length 13cm.
- Screw sets consist of M6 screw, Captive nut, Plastic washer. Screw and captive nut is Nickel plating.
- 19" FURUKAWA SERVER RACK are manufactured under ISO9001 : 2008 and ISO 14001 system.



		19" FURUKAWA SERVER RACK						
		U	15U	27U	36U	39U	42U	45U
W=60cm	Height							
	Depth		85cm	139cm	179cm	185cm	205cm	218.5cm
	60cm	F4-60615	F4-60627	F4-60636	F4-60639	F4-60642	F4-60645	
	80cm	F4-60815	F4-60827	F4-60836	F4-60839	F4-60842	F4-60845	
	90cm	F4-60915	F4-60927	F4-60936	F4-60939	F4-60942	F4-60945	
	100cm	F4-61015	F4-61027	F4-61036	F4-61039	F4-61042	F4-61045	
W=80cm	110cm	F4-61115	F4-61127	F4-61136	F4-61139	F4-61142	F4-61145	
	U	15U	27U	36U	39U	42U	45U	
	Height							
	Depth		85cm	139cm	179cm	185cm	205cm	218.5cm
	80cm	F4-80815	F4-80827	F4-80836	F4-80839	F4-80842	F4-80845	
	90cm	F4-80915	F4-80927	F4-80936	F4-80939	F4-80942	F4-80945	
100cm	F4-81015	F4-81027	F4-81036	F4-81039	F4-81042	F4-81045		
110cm	F4-81115	F4-81127	F4-81136	F4-81139	F4-81142	F4-81145		