

19" FURUKAWA DATA CENTER RACK

- 19" FURUKAWA DATA CENTER RACK design & produce under ANSI/EIA-310D – 1992 (Rev.EIA-310-C), IEC60297-1, IEC 60927-2, BS 5954 : Part2, DIN 41494 standard
- Modular knock down system for easily transport & assembly
- Produced from Electro-Galvanized Steel
 - Front – Rear, Side cover material thickness 1.5mm.
 - Mounting Angle Pole , Frame structure, Bottom Base material thickness 2.0mm.
 - Support base for Caster material thickness 3.0mm.
- Special design Mounting Angle Pole in C-shape for increasing strength for heavy equipment with square mounting hole size 9.5 x 9.5mm.
- Adjustable Mounting Angle Pole position with U screen for easily installation.
- Front door panel is special Curve design with Perforated hexagon hole . There are grey rubber attached for each door to protect dust. The security locks for front door is Swing handle
- Rear door panel is designed to be double door for easy to use and save space. Rear door is also perforated hexagon hole for quickly ventilating. The rear door come with security cam lock with master key system.
- Side Panels is solid steel come together with 2 Premium grade slide latches per panel and security cam lock with master key system
- Roof Cover also designed for installing up to 6 ventilating fan which compatible with 1x 4" , 2x4" , 3x4" fan set
- Bottom Base also designed to be 3 Parts Plinth which can support the heavy load. There are soft slide shutter function for all cables. Soft slide shutter also come with the soft grey sponge to protect insect and small animals to enter the rack from bottom.
- Adjustable Pedestal can levelling up to 180 degree for aligns on uneven surface. Levelling feet also cover with ABS material in order to protect Electrostatic and ground reason. Caster is Nylon six and 360 degree swivel plate which can be easily moving. Each caster can pass static load of 100 kg./caster.
- Rack Color is Black which using Electro static Powder Coating system
- For Grounding system also installing 2 ground cable size 2.5mm (Yellow-green color) length 18cm.connect the frame with front and rear door. For side panels also intall 4 ground cable (Yellow-green color) length 13cm.
- Screw sets consist of M6 screw, Captive nut, Plastic washer. Screw and captive nut is Nickel plating.
- 19" FURUKAWA DATA CENTER RACK are manufactured under ISO9001 : 2008 and ISO 14001 system.



19" FURUKAWA DATA CENTER RACK							
	U	15U	27U	36U	39U	42U	45U
	W=60cm	Height	85cm	139cm	179cm	185cm	205cm
Depth							
60cm		F5-60615	F5-60627	F5-60636	F5-60639	F5-60642	F5-60645
80cm		F5-60815	F5-60827	F5-60836	F5-60839	F5-60842	F5-60845
90cm		F5-60915	F5-60927	F5-60936	F5-60939	F5-60942	F5-60945
100cm		F5-61015	F5-61027	F5-61036	F5-61039	F5-61042	F5-61045
110cm		F5-61115	F5-61127	F5-61136	F5-61139	F5-61142	F5-61145
W=80cm	U	15U	27U	36U	39U	42U	45U
	Height	85cm	139cm	179cm	185cm	205cm	218.5cm
	Depth						
	80cm	F5-80815	F5-80827	F5-80836	F5-80839	F5-80842	F5-80845
	90cm	F5-80915	F5-80927	F5-80936	F5-80939	F5-80942	F5-80945
	100cm	F5-81015	F5-81027	F5-81036	F5-81039	F5-81042	F5-81045
	110cm	F5-81115	F5-81127	F5-81136	F5-81139	F5-81142	F5-81145