TECHNICAL SPECIFICATION 1954 - V 8 (04/11/2015)



CLOSED HORIZONTAL PLASTIC CABLE MANAGER 1U

	Product Type TELECOMMUNICATION INFRASTRUCTURE ACCESSORY		
	Product Family FISACESSO		
	Standard	RoHS Compliant	
Applications	Structured Cabling Systems, internal use, for installation in racks or brackets, vertical, or primary, in rooms or closetsprimary, or secondary, or for horizontal cabling in telecommunications rooms (cross-connect), the function of organizing and accommodation cables.		
Installation Environment	Indoor		
Operation Environment	Indoor non aggressive		
Compatibility	Cabinets 19"		
Warranty	12 months		
Advantage	 Made of High-Impact thermoplastic UL 94 V-0; Color: Black; Resistant and corrosion-protected product for the conditions specified for indoor use by (TIA/EIA-569); It features width 19" as the TIA/EIA-310E standard requirements; Has frontal manufacturer identification with icon; Has frontal cover that opens upwards and downwards; Ensures the perfect cable management, respecting the bend radius determined by TIA/EIA-568; Supports up to 24 cables U/UTP CAT.5e or CAT.6. 		
Constructive characteristic	·		
Width	482mm (19")		
Height	 Total: 1U Useful: 44.4mm 		
Depth	Total: 75mmUseful: 50mm		
Maximum weight	CAT.5e - (24 cables) CAT.6 - (24 cables)		
Material of Product body	High-impact thermoplastic		
Color	Black		
FURUKAWA	This info	ormative is from authorship and exclusive property of Furukawa Electric LatAm. Its integral or	



TECHNICAL SPECIFICATION 1954 - V 8 (04/11/2015)

Package

Package Type	Cardboard	
Amount per box gift	01 piece	
Amount per box (carton)	15 pieces	
Minimum order quantity	01 cardboard	
Dimension (WHD)	512 x 70 x 86 mm	
Associated Solutions	Management of cables and accessories	
Standards Compliance		
Standard	TIA/EIA - 569 C - COMMERCIAL BUILDING STANDARD FOR TELECOMMUNICATIONS PATHWAYS AND SPACES	
	TIA/EIA - 310 E - CABINETS, RACKS, PANELS, AND ASSOCIATED EQUIPAMENT	
Certifications	ETL (OFNR) Listed - Report N°: 100824709CRT-001 ETL (DMD) - Report N°: 3174638CRT-001	

